Model: Phoenix Pergola®

"AIR" & "FREE"



RETRACTABLE FABRIC ROOFS




Model: Phoenix Pergola® "AIR"




Application	Maximum Width	Maximum Projection	Options
Free Standing & Wall Mounted Commercial & Residential	5.5 m <i>/</i> 18' wide	7 m free standing 22' 11" proj. 10 m wall mount 32' 9" proj.	LEDS,


PRODUCT FEATURES:

- Retractable fabric roof pergola.
- Freestanding or wall mounted Pergola system suitable for small to medium sized patios.
- All aluminum frame powder coated
- Motorized all sizes.
- Optional hood system available.
- · Arched Fabric or sloping to one side.
- Powered with a Somfy Motor.














Phoenix AIR: Installations










PHOENIX "AIR" Pergola® Technical information









Crossbar Profile


Post Profile


Guide Profile

Dimensions:


I = Fabric assembly when retracted

Maximum post height is 270 cm (8' 8").






Standard Foot Plate





Adjustable Foot Plate Up to 4.5 cm


D	P cm / Ribs	Phoenix Air	
Pcm		1	Is
237,9	3	44	46
323,9	5	54	57
409,9	7	64	68
495,9	9	73	78
581,9	11	83	89
667,9	13	92	99
753,9	15	102	110
839,9	17	112	121
925,9	19	121	131
1000	21	131	142

PHOENIX AIR 01L: Self / Free Standing / 2 arches / 4 posts










Front View Two Arches


Side View Two Arches


System with 4 posts / 1 span fabric


L Max 5.5 meters / 18 ft. P Max 7m / 22' 11"

PHOENIX AIR 02L: Wall Mounted / 1 Arch / 2 posts










Front View Two Arches


Side View Two Arches


System with 4 posts / 1 span fabric

L Max 5.5 meters / 18 ft. P Max 7m / 22' 11"

PHOENIX AIR 01L: Self / Free Standing / 3 arches / 6 posts







Front View Three Arches


Side View Three Arches


System with 4 posts / 1 span fabric


L Max 5.5 meters / 18 ft. P Max 10 m / 32' 9"

PHOENIX AIR 02L: Wall Mounted / 2 Arches / 4 posts










Front View Three Arches


Side View Three Arches


System with 4 posts / 1 span fabric


L Max 5.5 meters / 18 ft. P Max 10 m / 32' 9"

PHOENIX AIR 01L: Self / Free Standing / 2 arches / 4 posts










Front View Two Arches


Side View Two Arches


System with 4 posts / 1 span fabric


L Max 5.5 meters / 18 ft. P Max 7m / 22' 11"

PHOENIX AIR 02L: Wall Mounted / 1 Arch / 2 posts










Front View Two Arches


Side View Two Arches


System with 4 posts / 1 span fabric

L Max 5.5 meters / 18 ft. P Max 7m / 22' 11"

PHOENIX AIR 01L: Self / Free Standing / 3 arches / 6 posts







Front View Three Arches


Side View Three Arches


System with 4 posts / 1 span fabric


L Max 5.5 meters / 18 ft. P Max 10 m / 32' 9"

PHOENIX AIR 02L: Wall Mounted / 2 Arches / 4 posts









Front View Three Arches

Side View Three Arches

System with 4 posts / 1 span fabric

L Max 5.5 meters / 18 ft. P Max 10 m / 32' 9"

Model: Phoenix Pergola® "FREE"



	Application	Maximum Width	Maximum Projection	Options
A STATE OF THE PARTY OF THE PAR	Free Standing & Wall Mounted Commercial & Residential	5.5 m / 18' wide	6m free standing 19' 8" proj.	LEDS,

PRODUCT FEATURES:

- Retractable fabric roof pergola.
- Freestanding or wall mounted Pergola system suitable for small to medium sized patios.
- All aluminum frame powder coated
- Motorized all sizes.
- Optional hood system available.
- Arched Fabric or sloping to one side.
- Powered with a Somfy Motor.




Phoenix FREE: Installations













PHOENIX "FREE" Pergola® Technical information










Post Profile


Guide Profile

Dimensions:


I = Fabric assembly when retracted

Maximum post height is 270 cm (8' 8").





Standard Foot Plate




Adjustable Foot Plate

Jp to 4.5 cm	า
•	

9	Described to the	Phoenix Free	
P cm	Rompitratta / Ribs	I	Is
237,9	3	48	51
323,9	5	57	61
409,9	7	67	72
495,9	9	77	83
581,9	11	86	93

PHOENIX FREE 01L: Self / Free Standing / 4 posts




Side View


System with 4 posts / 1 span fabric


Front View


L Max 5.5 meters / 18 ft. P Max 6 m / 6' 8"

PHOENIX FREE 02L: Self / Wall Mounted / 2 posts










Front View Side View

System with 2 posts / 1 span fabric

L Max 5.5 meters / 18 ft. P Max 6 m / 6' 8"

PRATIC PERGOLA® FEATURES AND PATENTS





Pergola model chosen.



The patented drip catcher keeps water from flowing off the sides when the wind is pushing water sideways. Instead the water will flow off the front or into the gutter (Traditional Pergola models only).







The patented click system allows for easy and safe installation of the fabric and fabric ribs to the frame carriages using an easy click and lock system. This patented safety box for the motor installs on the frame with an extra mounting profile. This feature keeps the fabric perfectly straight even in temperature variations. The device makes operating easy and quieter and also stops the motor from operating in case of excessive force. The box is ideally suited for Somfy RTS Altus motors with remote controls (Traditional Pergola models only).



NOTE: Features will depend on



STANDARD FRAME COLORS FOR ALL PHOENIX MODELS:





CORTEN Coarse



IRON GREY
Coarse

OPTIONAL



FULL RAL COLOR RANGE / EXTRA COST


NOTE: These eight (8) colors are "super durables" which offer better durability compared with standard polyesters powders.



NOTE: ACTUAL FRAME COLOR MAY VARY FROM DIGITAL IMAGES

602 FLEX LIGHT CLASSIC / OPAQUE COLORS

STANDARD









602-8503-98" White 602



602-50020-98" Cream 602

The Precontraint 602 fabric from Ferrari offers excellent dimensional stability with minimal stretching and exceptional dirt resistance thanks to a PVDF topcoat on both sides. The fabric is therefore perfect for use on retractable Pergola® roof awnings. The fabric is 22.1 oz/sq. yard with a Glossy finish. The two standard opaque colors above are the most commonly used and is standard on all Pergola® awnings. The two above colors are opaque and do not allow light to go through the fabric. Fabrics are Fire Retardant and certificate is available.

OPTIONAL PERGOLA & SCREEN FABRIC COLORS

502 PROOF SOLTIS / OPAQUE SATIN FINISH COLORS

The Precontraint 502 fabric from Ferrari also offers excellent dimensional stability with minimal stretching and exceptional dirt resistance thanks to a PVDF topcoat on both sides. The fabric is therefore perfect for use on retractable Pergola® roof awnings. The fabric is 16.8 oz/sq. yard with a satin finish. Fabrics are fire retardant and certificate is available.









Serge Ferrari


14 % Open Screen Mesh

Raso Screen





86-2043 Bronze




86 – 2135

Sandy Beige




86 - 2053

Black




86 – 2175 Champagne




86 – 2044

White



86 - 2012

Pepper



86 - 2171

Boulder

Technical properties

Openess factor	14%	
Weight	380 g/m² — 11.2 oz/sqyd	
Thickness	0.45 mm — 450 microns	
Width	177 cm - 267 cm — 69.7 in 105.1 in.	

Superior elongation and tear resistance

No deformation during processing and use

Superior aesthetic and mechanical durability

Smooth finish easy to clean, space saving, easy rolling

MOTORIZATION & AUTOMATION



Note:

Opera and Vision Louvered systems uses a different Linak motor and remote.

The Sunair PERGOLA® program features SOMFY RTS motor with an integrated radio receiver that allows you to operate the awning or screen by remote control with a wall mounted or hand held remote and by a smart phone device.

With a simple click of a button on your remote, the awning or shade will extend, retract, lower or raise automatically.



1 through 16 channel wall mounted and hand held remotes are available













PHOENIX PERGOLA® MOTORS



Sunair uses Somfy motors and controls for their Pergola awnings in the following range

Altus 525/530 Phoenix Air and Free



All Somfy Motors are UL and CSA Recognized

· All SOMFY motors are UL Recognized and can be found under the following file numbers:

E60495, E60888, E63714









	JZJMZ	JJUN2
Torque	25 Nm	30 Nm
Nominal Voltage	120V/60Hz	
Rated Current	1.6A	1.5A
Speed	20 rpm	14 rpm

52542

Type of power cable

RTS 120V AC / 60Hz 3 conductor cable



white = neutral

black = hot

520D2


green = ground



Radio Technology Somfy

Radio Technology Somfy® (RTS) allows wireless radio control of motorized applications via the RTS family of controls.

MOTOR SAFETY BOX DIMENSIONS






SOLIRIS RTS 24V KIT Sun & Wind Sensor

The Soliris RTS Sun and Wind Sensor automatically controls your RTS motorized products based on current weather conditions.



ONDEIS® WIREFREE Sun & Rain Sensor

The Rain Sensor is a solar-powered combined rain and sun sensor compatible with Radio Technology Somfy® motorized exterior products, including awnings and screens.



DRY CONTACT INPUT RTS TRANSMITTER

Dry Contact to RTS interface can be used to communicate between home automation or other third party systems like fire alarms to retract screens in an emergency. Can be interfaced with a physical switch (Battery powered. Battery designed top last at least 2 years.

The Somfy myLink™ is a simple device that turns your smartphone or tablet into a sophisticated remote control for motorized products featuring Radio Technology Somfy®, allowing you to operate them whether you're home or not. Combine all the benefits of Somfy's RTS hand-held remotes and timers in a convenient app.










PHOENIX LED OPTIONS:



LED / WHITE only or RGB Perimeter



REMOTE CONTROLLED

SET FLOORING:



PRODUCT FEATURES:


- Platform decking designed to be integrated with Bioclimatic Pergolas like Opera,
 Vision, Brera, Nomo, and Rialto.
- Sits on an existing supported concrete floor.
- Made to fit Pergola awning system.
- Assembled in place.
- Can be fitted with different flooring types.







Note: Sunair® reserves the right to change engineering, specifications and prices without notice. Images and Illustrations in the catalog may vary from digital and printed manuals. Sunair® is not responsible for printed inaccuracies in this manual.





SUNPROOFING AMERICA!



MARYLAND LOCATION

Mailing: P.O. Box 1068 Shipping: 7785 Rt. 175

Jessup, MD 20794

Toll Free 800 - 548 - 0408

Phone: 410 - 799 - 1145

Fax: 410 - 799 - 5584

ARIZONA LOCATION

Mailing: Same as Jessup

Shipping: 3807 West Thomas Rd.

Phoenix, AZ 85017

Toll Free 877 - 272 - 3920

Phone: 602 - 272 - 3920

Fax: 602 - 272 - 3925

www.sunairawnings.com

info@sunairawnings.com