

SOLHARO®

For glass Conservatories, Sun Rooms, and wood trellis Pergolas


The Solharo® is the ideal solar protection solution for sunrooms and conservatories and wood Trellis Pergolas. With a standard motor, the shade will automatically extend to shade and lower the temperature in the room. The system is designed for solar control and can only be used in rain if configured with mesh fabric only so water goes through it and does not collect.

Туре	Standard Frame Colors	Standard Widths	Standard Projections	Recommended Applications	Recommended Fabrics
Tensioned Track System Conservatory Shade	9 standard Sunair colors	Through 27' Split multiple bays See price list	5' through 19' 8" See Price list	Conservatory rooms and wood structures Retractable	Soltis 86 & 92 Mesh Sunbrella / Para


- Protects against the sun and lowers the temperature in the sun room, significantly lowering cooling costs.
- Used for sun protection and solar control only (Not for rain protection unless mounted on a 45 degree slope).
- The fabric blocks the sun before it hits the glass for more effective solar control.
- Prevents fading of your furniture, carpets, curtains, and wallpaper.
- Can cover small to large sun rooms & wood structures.
- Great for residential and commercial applications.
- Easy motorized operation standard.
- Hundreds of fabric or mesh colors to choose from.



Revised 02/15/2023




MEASURING SOLHARO




The most important measurement is the measurement center to center of each beam of the structure. All orders must be submitted with the Solharo work sheet showing dimensions. The Solharo will then be manufactured with the guides or tracks running center of the beams. From the center of the outside lateral guides, the system extends 1" on each side (see illustration above). If multiple bays are required indicate where the center of each track needs to be. The bays can vary in size and it is not necessary to have each bay the same size. Consult the office if a bay is less than 6'7". The system can not extend down and around the curve. For best coverage you can extend the track 12" straight beyond the curve of the sunroom.







The aluminum housing containing the roller system is 6 $\frac{1}{2}$ " inches high or 165 mm high with the brackets. Different mounting situations can be accommodated (See further technical documents).



Note: Dimensions in metric mm



SOLHARO® EXPLODED VIEW





NOTE: All these colors except Green Ral 6005 and Desert Sand / Ivory are "super durables" which offer better durability compared with standard polyesters powders.



NOTE: ACTUAL FRAME COLOR MAY VARY FROM DIGITAL IMAGES






ACRYLIC FABRIC COLLECTION




Fabric covers sewn with Tenara thread.












Graduated

5398/930 Dune / Browi Striped





Grey

bie

SOLIDS · TWEEDS · BLOCK STRIPES · FANCY STRIPES · GRADUATED STRIPES

5	Forest Green	4
7	Moss Green	4
8	Medium Green	-
11	Red	
12	Yellow	4
13	Ocean Blue	40
14	Toast	42
15	White	50
24	Black	5
33	Forest Green/White	50
35	Red/White	5
37	Yellow/White	50
47	Brown/Stone	5
52	Tan	50
53	Pale Peach	50
73	Burgundy	50
75	Navy Blue	5
79	Grey	5
81	True Brown	50
84	Dark Terracotta	51
87	Fancy Blue	51
101	Elite Toast	51
102	Cappuccino	5
106	Toffee	5
107	Textured Dark Grey	51
242	Grey/White	53
426	Terracotta	53
439	Dark Grey/White	53
809	Cream/Green	53
878	Beige/White Speckled	53
926	Taupe Classic Solid	534
931	Green/Cream Wide	534
969	Grey Fancy Stripe	
1101	Beige/Stripe Fancy	
1120	Brown/Beige Fancy	537
1150	Rust/Green Multi	
116/15	Medium Blue/White	53
1243	Yellow Multi	539
1302	Sage Tweed	53
1330/512	Carbon Stitch	53
15/1	Beige	539
15/14	Raw	539
15/79	Stone	539
4015/91	Raw Speckled	53
407/11	Burgundy Tweed	53
407/13	Blue Tweed	53

407/14	Toast Classic Tweed
407/16	Moss Classic Tweed
407/3	Green Classic Tweed
407/6	Green Tweed
407/79	Pepper Grey
07/926	Grey Classic Tweed
215/15	Textured Tan
5000/57	Cocoa Stripe
5001/1	Green Graduated
5001/13	Blue Graduated
5001/7	Moss Graduated
5001/73	Burgundy/Grey Graduated
5009/1	Beige/Tan Stripe
5009/14	Brown/Tan Stripe
500 <i>5/</i> 14 5011/11	Brick/Natural Fancy
5011/57	Tan/Brown Fancy
	Tan/Green Fancy
5011/7	Natural/Moss Graduated
5071/7	
072/86	Brown/Stone Fancy
5118/62	Yellow/White Fancy
5144/14	Pastel/Natural Fancy
5167/11	Red/Grey Fancy
5167/2	Blue/Grey Fancy
5167/5	Green/Grey Fancy
5173/12	Yellow/Grey Stripe
5304/15	Rose/Grey Stripe
5347/58	Grey/Wheat Multi
5347/79	Platinum Grey Multi
5348/58	Beige/Wheat Multi
5348/79	Grey/Slate Multi
849/106	Brown/Cream Stripe
849/930	Beige/Brown Classic
5369	Charcoal/Brown
5370	Beige/Grey
371/727	Grey/Black Stripe
5374	Smoke/Grey Stripe
5396/78	Green Tweed Stripe
896/930	Hazelnut Stripe
5396/97	Charcoal Tweed Stripe
5397/97	Grey/Black Graduated
898/107	Carbon Blue Blend
898/930	Dune/Brown Stripe
899/107	Dark Grey Tweed
5399/15	Light Grey Stripe
5399/52	Sesame Tweed Stripe
5399/94	Stone/Grey Tweed
	-

5406/52	Coriander Tweed
5406/94	Textured Desert Beige
5407/107	Charcoal/Stone Tweed
5407/15	Textured Silk Grey
5407/17	Sky Tweed
5407/52	Sesame Tweed
5407/94	Desert Grey Tweed
633/79	Grey/Black Fancy
634/51	Grey/Natural Fancy
634/97	Green/Tan Fancy
635/11	Cranberry/Natural Fancy
636/10	Grey/Blue Graduated
636/12	Yellow Graduated
636/14	Brown Elite Stripe
636/5	Green/Beige Fancy
636/84	Terracotta Graduated
638/5	Green/Grey Fancy
639/99	Tan/Natural Fancy
641/10	Blue/Beige Fancy
727/15	Textured Medium Grey
739/701	Sage/Beige Fancy
769/75	Cream/Blue Fancy
782/14	Beige Solid Classic
873/151	Dune Tweed
873/2	Textured Cocoa
939/94	Grey Elite Stripe
940/5	Green Elite Stripe
947/14	Pale Beige Classic
949/91	Brown/Beige Classic
950/24	Grey/Charcoal Classic
951/92	Grey/Navy Classic
967/926	Grey/Charcoal Elite
968/426	Terracotta/Cream Fancy
97/84	Plum
986/106	Textured Beige
986/15	Textured Light Grey
986/727	Textured Pebble Grey
	-



Soltis Horizon 86



14 % Open Screen Mesh

Exterior Screen Fabric

5 year warranty from Ferrari



Exterior Screen Fabric TEXTILE NONO[™]9 BRAND FABRIC 5 % Open Screen Mesh ShadowTexture Granite **Expresso** Texture White Stone Texture Flat Black Bone Tobacco Charcoal

TEXTILENE[®] nano[™] 95 is a durable, yet lightweight synthetic fabric. It is lighter and finer with the same technical qualities as the original TEXTILENE[®]. TEXTILENE[®] nano[™]95 is excellent for exterior use and can reduce energy costs while blocking up to 95% of the sun's harmful rays.





Product Specifications Sheet





Sunair is proud to offer the full line of Somfy motors and controls for our awnings and screens program SOMFY RTS features motors with an integrated radio receiver that allows you to operate the awning by remote control with a wall mounted or hand held remote or by smart phone device. With a simple click of your remote, the awning or shade will extend or retract automatically. The manual override Sunea motor is ideal for awnings and the Altus motors is ideal for exterior screens. Each motor can be configured with a cord & plug which can simply be plugged into your patio outlet. They are available in 1.4", 11', 17', & 23' lengths. Altus motor cords depend on motor model and is standard either 6' or 10' pigtail cords. Optional Altus plug in cords are available in 10', 18', and 24 ' lengths. Optional screen motor is Maestria with obstacle detection. Add Tahoma smart phone and table interface.



SOMFY REMOTES:



One (1) through (16) channel hand held or wall mounted remotes are available. <u>Remotes are available in</u> <u>different colors to suit your style,</u>

<u>please inquire.</u>



Telis hand-held remotes offer convenient and simple operation of every type of motorized application. Channels help organize the motorized products that are operated. Single channel remotes can operate one individual product or one group of motorized products. Multiple channel remotes can handle groups of motorized products.



AVAILABLE AUTOMATIC SENSORS & CONTROLS



SOLIRIS RTS 24V KIT Sun & Wind Sensor

The Soliris RTS Sun and Wind Sensor automatically controls your RTS motorized products based on current weather conditions.



ONDEIS® WIREFREE Sun & Rain Sensor

The Rain Sensor is a solar-powered combined rain and sun sensor compatible with Radio Technology Somfy[®] motorized exterior products, including awnings and screens.



Sunis & ThermoSunis Indoor WireFree™ RTS Sensors



SOMFY MOTOR WIRING



The three (3) wire cords can be wired in parallel and can be ordered with a molded plug to simply plug into an exterior UL approved GFI outlet. The standard four (4) wire cords must be hard wired with a traditional toggle wall switch. Screens can not be ordered with molded plugs on the end.



Radio Technology Somfy

Optional molded plug

is available for

"awning" motors only

Radio Technology Somfy® (RTS) allows wireless radio control of motorized applications via the RTS family of controls.

> RTS 120V AC / 60Hz 3 conductor cable


All Somfy Motors are UL and CSA Recognized

 All SOMFY motors are UL Recognized and can be found under the following file numbers:

E60495, E60888, E63714







white = neutral black = hotgreen = ground


Type of power cable STANDARD Hardwire motor cord

Wired 120V AC / 60Hz 4 conductor cable

Type of power cable

white = neutral red = direction 1 black = direction 2 green = ground

RTS plug in capable motor cord






LT50 Altus® RTS

Solharo Type 1 & 2

Dimensions




2 mounting holes for self tapping screws. Dia. 5 mm (cat #967001 Depth 13 mm spaced 1.89" (48 mm) apart.





506	510	525	535	550
6 Nm	10 Nm	25 Nm	35 Nm	50 Nm
120V / 60HZ				
1.1A	1.3A	1.6A	2.1A	2.1A
38 rpm	38 rpm	20 rpm	20 rpm	14 rpm



LT60 Altus RTS



LT60 Standard

Performances	660R2
Torque (in. Ibs.)	60 Nm (530 in. lbs.)
Nominal Voltage	120V/60Hz
Rated Current	2.5A
Speed	14 rpm
Thermal Protection	4 minutes
Radio Frequency	433.42 MHz
Sound Level	≤ 63 dBA

Performances660 R2Torque (in. lbs.)60 Nm (530 in. lbs.)Nominal Voltage120V/60HzRated Current2.5ASpeed14 rpmThermal Protection5 minutesSound Level≤ 63 dBA



4 x Ø 5 mm - 12 mm long steel pop rivet or screw, 90° apart.

Somfy TaHoma[®] RTS Smartphone and Tablet Interface

The Somfy TaHoma[®] gateway and smart phone app provides convenient and customized control of Somfy powered motorized shades, blinds, and other motorized solutions. Control up to 40 RTS (Radio Technology Somfy) channels using the TaHoma app. Multiple TaHoma devices can be joined for multi-zone control.



- North America app, you can remotely activate both Zigbee and RTS products Supports UP/ DOWN/MY/STOP commands for motorized shades/blinds.
- Supports incremental control for Tilt motors and lighting I Supports ON/OFF commands for control of lighting or other devices powered via the Zigbee Smart Plug Multiple users .
- Remote access Control4[®] Certified
 Integration with third-party systems over IP
 Compatible with Somfy Synergy[™] API





TaHoma® RTS

Bond Home / Smartphone and Tablet Interface

Bond Bridge and Bond Bridge Pro works as a bridge between Wi-Fi and your remotes recorded signal allowing you to operate your Sunair shades, awnings, pergolas, ceiling fans, fireplaces and more with the Bond app. Works with Somfy and other motor manufacturers.



Remote control from anywhere

Be able to control everything even from outside your home.

Bond Bridge

- Works with Alexa, Google Home, and SmartThings,
- Remote Control via Bond Home app
- Works with iPhone or Android
- No installation needed
- Smart home functionality without breaking the bank

Bond Bridge Pro: Added features...

- Ethernet port & PoE technology
- Smart home integrations
- Ceiling and wall mount

OPTIONAL:

• <u>Sidekick for Shades</u>: 5-channel Shade and awning

BOND REMOTE SWITCH:

Sidekick for Shades/Awnings: 5-channel Shade Keypad



o bond

- Wireless flush mount shade remote.
- Communicates directly with the shade.
- 10-year battery life.
- Set up shade limits no manufacturer remote required.
- This version of Sidekick does not support Scene Keypad functionality.
- 10-year battery life.
- Install with or without a workbox (flush mount).
- 5-channel control.
- Set up shade limits no manufacturer remote required.

Notes

Note: Sunair[®] reserves the right to change engineering, specifications and prices without notice. Images and Illustrations in the catalog may vary from digital and printed manuals.





SUNPROOFING AMERICA!



MARYLAND LOCATION

Mailing: P.O. Box 1068 Shipping: 7785 Rt. 175 Jessup, MD 20794

Toll Free	800	- 548 -	0408
-----------	-----	---------	------

- Phone: 410 799 1145
- Fax: 410 799 5584

www.sunairawnings.com

ARIZONA LOCATION

Mailing: <u>Same as Jessup</u> Shipping: 3807 West Thomas Rd. Phoenix, AZ 85017

Toll Free	877 - 272 - 3920
Phone:	602 - 272 - 3920
Fax:	602 - 272 - 3925

info@sunairawnings.com