







Adjusting the Limits

To change the lower limit:

Move the motor to its current lower limit position and let it stop. Press the  and  buttons simultaneously until the motor jogs, then release. Adjust to a new lower limit position. Press the  button until the motor jogs, then release. Check new limit.

To change the upper limit:


Move the motor to its current upper limit position and let it stop. Press the  and  buttons simultaneously until the motor jogs, then release. Adjust to a new upper limit position. Press the  button until the motor jogs, then release. Check new limit.

To add a remote/channel or sun and wind sensor:

First press the programming button on the back of the already programmed remote until the motor jogs. Then press the programming button on the remote or sun/wind sensor that you would like to add until the motor jogs. Check it.

To reset the motor:

you will need to disconnect power (120vac) for 2 seconds, reconnect for 10 seconds, disconnect for another 2 seconds and reconnect. The motor should start to move and then stop on its own (If this does not happen, continue to perform the disconnects until it does). Once the motor stops moving on its own, press and hold the programming button on the back of the remote and count to ten without letting go. The motor should jog twice.



Advanced Features/Functions

BACK IMPULSE function for both cassette and standard awnings

This function allows you to apply tension on the fabric when the awning is fully extended. The motor can be adjusted up to a 1/2 half turn.

To activate this function:

STEP 1

Set the awning to the lowest position.



STEP 2

Press the MY and Up buttons until the awning jogs: The motor is in programming mode.



STEP 3

Adjust the fabric's tension using the Up or Down buttons.



STEP 4

Press the MY button until the awning jogs: The fabric's tension has been programmed.



BACK RELEASE function on cassette awnings only

This function allows the fabric tension to be released after the cassette awning is closed.

To activate this function:

STEP 1

Cut the power, unless you are using the awning in the first 4 cycles.

STEP 2

Set the awning to the inner limit position.



STEP 3

Press the MY and Down buttons until the motor moves up and down: If the Back release function was deactivated, it is activated. If the Back release function was active, it is deactivated.



CLOSING FORCE function on cassette awnings only

This function enables the closing force of the cassette awning to be increased or decreased to 3 levels (high/medium/low). The motor is factory set at the medium level.

To activate this function:

STEP 1


Cut the power, unless you are using the awning in the first 4 cycles.

STEP 2

Bring the awning to the halfway position.

STEP 3

Briefly press the MY and Up buttons simultaneously, then immediately press and hold the MY and Up buttons until the motor jogs. The motor is only in programming mode for approx. 10 seconds.



STEP 4

Adjust the closing force setting using the Up and Down buttons.
 - to increase the closing force, press the Up button until the motor jogs up and down.
 - to decrease the closing force, press the Down button until the motor jogs up and down.
 (long jog for levels 3 and 1) (short jog for level 2)



Increases closing force



Decreases closing force

STEP 5

Press the MY button until the awning jogs up and down: The new closing force has been programmed.

