

Model: Zen Pergola®


Revision 01/29/2019



Standard Frame Colors	Maximum Width	Maximum Projection	Options
8 Akzo Nobel colors plus optional custom RAL colors	4.5 m / 14' 9" wide	5.5 m / 16' 5" proj.	LEDs, Undercovers

PRODUCT FEATURES:


- Retractable fabric roof pergola.
- Freestanding Pergola system suitable for small sized patios.
- All aluminum frame powder coated.
- Manual operation all sizes.
- V cover water drainage to one or both sides.




Zen: Installations



ZEN Pergola® Technical information




Standard taut alternating V cover




Note The total dimension of the awning is $L + 12$.


Ground plate



Guide profile
cod. 2861



Post and supporting
bar cod. 2799



Dimensions table

P cm	No. of Layers	I cm
200	4	44,1
250	6	53,5
300	6	53,5
350	8	62,9
400	8	62,9
450	10	72,3
500	12	81,7

The number of ribs shown in the table is approximate.

Legend

P: Total depth

L: Width


I: Closed awning size

H: Height at the lower edge of the front rib profile. Standard
H = 230 cm

TYPE ZEN 2 Arches system with 4 posts / 1 span fabric


L = width = from 6' 7" to 14' 9" wide

Side view




P_o/A_o min 40 cm - max 120 cm
 $D1 > P_o + A_o$


View from above




Front view



PERGOLA® ZEN



PRATIC PERGOLA® FEATURES AND PATENTS



The patented drip catcher keeps water from flowing off the sides when the wind is pushing water sideways. Instead the water will flow off the front or into the gutter.




The patented click system allows for easy and safe installation of the fabric and fabric ribs to the frame carriages using an easy click and lock system.




STANDARD FRAME COLORS FOR THESE PERGOLA MODELS:

*Nomo, Rialto, Opera, Vision, Phoenix, Zen,
Alutecnic, Stil, Evo, & Wood Plus (metal components)*

NOTE: Optional for OPERA & VISION is to have Structure and louvers in two different colors.




WHITE Gloss
Ral 9010



WHITE SAND
Coarse Ral 9016



IVORY SAND
Ral 1013 Coarse




IVORY / SEMI
Gloss Ral 1013



GREY SAND
Gloss Ral 9006



BRIGHT ALUM
Matt Ral 9006




CORTEN
Coarse



IRON GREY
Coarse

OPTIONAL



FULL RAL COLOR
RANGE / EXTRA
COST

8 Akzo Nobel Colors

AkzoNobel

NOTE: ACTUAL FRAME COLOR MAY VARY FROM DIGITAL IMAGES




PERGOLA STANDARD FABRIC COLORS

602 FLEX LIGHT CLASSIC / OPAQUE COLORS




602N-8503 / 8103



602N-50020

The Preconstraint 602 fabric from Ferrari offers excellent dimensional stability with minimal stretching and exceptional dirt resistance thanks to a PVDF topcoat on both sides. The fabric is therefore perfect for use on retractable Pergola® roof awnings. The fabric is 22.1 oz/sq yard with a Glossy finish. The two standard opaque colors above are the most commonly used and is standard on all Pergola® awnings. The two above colors are opaque and do not allow light to go through the fabric. The 602 is also available standard in the 10 each translucent colors below allowing some light to go through. Fabrics are Fire Retardant and certificate is available.



Serge Ferrari

NON STANDARD PERGOLA FABRIC COLORS


502 PROOF SOLTIS / OPAQUE SATIN FINISH COLORS

The Preconstraint 502 fabric from Ferrari also offers excellent dimensional stability with minimal stretching and exceptional dirt resistance thanks to a PVDF topcoat on both sides. The fabric is therefore perfect for use on retractable Pergola® roof awnings. The fabric is 16.8 oz/sq. yard with a satin finish. Fabrics are fire retardant and certificate is available.

									
502V2-8102C	502V2-2171C	502V2-2168C	502V2-2167C	502V2-8450C	502V2-8341C	502V2-8861C	502V2-50265C	502V2-2135C	502V2-2141C
									
502V2-2138C	502V2-2012C	502V2-2148C	502V2-2137C	502V2-2158C	502V2-50668C	502V2-50669C	502V2-50670C	502V2-8056C	502V2-2156C
									
502V2-2152C	502V2-8255C	502V2-2150C	502V2-8204C	502V2-2172C	502V2-20185C	502V2-50674C	502V2-2166C	502V2-50671C	502V2-50675C
									
502V2-50672C	502V2-50676C	502V2-50270C	502V2-50673C	502V2-50677C	502V2-2160C	502V2-2161C	502V2-1125C	502V2-2157C	502V2-8284C

satin finish


Serge Ferrari




HEATERS: COSY 1500 AW Sleek, Low clearance, infrared heaters.

Sunair® awnings do not specify any particular brand of heaters but we do offer the Solaira brand as a convenience and as “supply” only. As supply only all warranty is per the Manufacturer (Solaira). Please see separate manufacturers installation, use, servicing and warranty documents. Mounting and wiring the heaters on the Pergola units is not included and will be the responsibility of the dealer / customer in the field during installation. Check your local codes for correct wiring instructions. All heaters should be installed by a certified electrician to local state electrical codes. See separate manufacturer’s data sheet and wiring instructions. If you purchase your own heaters, make sure that the heater brand and model you chose can be installed within the pergola unit to code. Aluminum Brackets to install the heaters on the awning are sold separately. Note: Sunair® awnings can only make suggestions but will not be responsible or warranty the performance and the effectiveness of the heaters. Check with the manufacturer of the heaters for the recommended number of heaters for your application and best installation position of the heater for best results.

Con’t next page

Solaira Heaters con't

Note: Specifier / Customer must contact Solaira for recommended heater number and position.



HEAT COVERAGE EXAMPLES

Model	A	B	C	D	Heat Zone*	Heat Density*
SCOSYXLAW15120 B/W	6'7"	9	8	11	90 sq. ft.	16 watt/sq. ft.
SCOSYXLAW15240 B/W	6'7"	9	8	11	90 sq. ft.	16 watt/sq. ft.
SCOSYXLAW20240 B/W	8'2"	9	8	11	90 sq. ft.	22 watt/sq. ft.
SCOSYXLAW-L15240 S	6'7	9	8	11	90 sq. ft.	16 watt/sq. ft.
SCOSYXLAW-L20240 S	8'2"	9	8	11	90 sq. ft.	22 watt/sq. ft.

*Heat Zone and actual heat density will vary based on mounting height and angle of heater (Overhead mounted zones will be different than this guide). Please use this as a guideline only and contact Solaira for a more detailed specifier guide.

Con't next page

Solaria Heaters con't

240 VOLT: 1.5Kw 208 - 240 V

Heater Model Black # SCOSYAW15240B Ral:9005

Heater Model White # SCOSYAW15240W Ral:9010

110 VOLT: 1.5Kw 120V


Heater Model Black # SCOSYAW15120B Ral: 9005

Heater Model White # SCOSYAW15120W Ral:9010

ADD CONTROLER AND ENCLOSURE BELOW TO BOTH HEATER MODELS ABOVE:

Controller #SHP18280SOL

Enclosure #SHP80ENCLOSE




NOTE:

Maximum 6 ea. 110 volt heaters can be used per controller and box.

Maximum 12 ea. 240 volt heaters can be used per controller and box.

STARLED “Classic” 130 cm / 51” White LED bars

For wall mounted Pergola awnings only (Not for Nomo, Rialto, Opera or Vision).



StarLed is the high efficiency led light that allows you to create an intimate, picturesque and bright room under the pergolas

- ✓ Led bar length 130 cm. 140 Led per m., 24 V, PW 14 W
- ✓ Opaline polycarbonate tube 15x15mm
- ✓ Closing caps
- ✓ Installation with screws and adhesive tape 3M
- ✓ Light colour @3000°K
- ✓ Light emission: @1050 lumen
- ✓ High efficiency, warm light Led. Lumen - power ratio is very high, about @110lm/W
- ✓ On request with radio control.

Recommended # of lights: There is no fixed rule how many lights are recommended as it depends on how much light the customer needs. Typically three to four (3 to 4) lights is enough per section of each Pergola or per bay.

LED Soft / White Custom sized LED bars White

For wall mounted Pergola awnings

5MM ILUMA™ LIGHT STRIPS



The soft white LED lighting strips are available up to 40 ft long (Maximum allowable amount of linear lighting per Somfy Lighting receiver). One Somfy lighting receiver #1811486 is needed per 40 ft. of linear LED lighting. Typically two to four (2 - 4) lighting bars are centered per each bay or section of Pergola. Multi Channel Telis remotes are needed for the LED lighting depending on how many lighting receivers are needed.



UNDERCOVERS WALL MOUNTED PERGOLA® AWNINGS






To create a nice atmospheres with wall Pergola® Awnings , it is possible to apply an "Undercover" installed under the ribs. Please note fabric will hang lower than top Vinyl cover. This undercover will be slightly narrower than the top cover by at least 4" / 10 cm per side to prevent water from going up along the PVC flap and wet the fabric of the under cover (Solid 60" fabric colors only).

AVAILABLE FABRICS:


Standard: Sunbrella 60" solid colors.

Optional:

Fire retardant Sunbrella & Tempotest STAR 60" solid colors from range.




PLease note rib spacing will increase 6mm / 5/16" between each fold in the fabric.




Note: Undercovers are installed with a "clip" system.

UP & DOWN Glass Walls Options



The Up & Down model is made up of two sections, one stationary and one mobile. A simple key is used to lock and release the module. To raise, release window with the key and the spring loaded module will slowly rise on its own.



The Up and Down model of our glass window dividers can be customized to match your color scheme or even display your logo! The base aluminum colors are White and Iron Grey colors. Virtually any color and design graphic motifs can be added to the glass to showcase your restaurant's unique style. Other models are also available.




Installations



NOTES:

NOTES:

Note: Sunair® reserves the right to change engineering, specifications, and prices without notice. Images and Illustrations in the catalog may vary from digital and printed manuals. Sunair® is not responsible for printed inaccuracies in this manual.



SUNPROOFING AMERICA!



MARYLAND LOCATION

Mailing: P.O. Box 1068

Shipping: 7785 Rt. 175

Jessup, MD 20794

Toll Free 800 - 548 - 0408

Phone: 410 - 799 - 1145

Fax: 410 - 799 - 5584

ARIZONA LOCATION

Mailing: Same as Jessup

Shipping: 3807 West Thomas Rd.

Phoenix, AZ 85017

Toll Free 877 - 272 - 3920

Phone: 602 - 272 - 3920

Fax: 602 - 272 - 3925

www.sunairawnings.com

info@sunairawnings.com