


300
Black-Black
2025 SUNAIR
STOCK COLOR




000
White-White
Special Order



001
White-Linen
Special Order



004
White-Pearl Gray
Special Order



700
Anthracite-Anthracite
2025 SUNAIR
STOCK COLOR





307
Black-Bronze
2025 SUNAIR
STOCK COLOR

Solar Heat Control Properties

REF.	COLOR	TV n-h (%)	TS (%)	RS (%)	AS (%)	GTOT INT.	GTOT EXT.
000	WHITE WHITE <i>S.O.</i>	16.9	19.8	69.2	11.0	0.35	0.14
001	WHITE LINEN <i>S.O.</i>	13.3	16.8	60.3	22.9	0.37	0.13
004	WHITE PEARL GRAY <i>S.O.</i>	10.6	13.9	51.9	34.2	0.40	0.12
300	BLACK BLACK <i>STOCK</i>	1.5	1.5	4.0	94.5	0.55	0.10
307	BLACK BRONZE <i>STOCK</i>	2.4	2.5	6.4	91.1	0.55	0.10
700	ANTHRACITE ANTHRACITE <i>STOCK</i>	2.3	2.6	7.7	89.7	0.54	0.10

TV: Visible light transmission / TS: Solar transmission / RS: Solar reflection / AS: Solar absorption / GTOT: Total solar energy transmittance



V.10.2024

Specifications

Composition: 30% Polyester, 70% Vinyl

Syle: Basket Weave

Mesh Weight: 14 (oz/yd²)

Openness Factor: 1 %

Fabric Thickness (in): .020

Width: 118"

Fire classification: NFPA 701 Test 1, and CA Fire Marshall Title 19, Section 1237.1

Warranty: 10 years exterior

Bacteria and Fungal Resistance: AATCC Test Method 100-2012

Energy Saving:

Considerable reductions in energy consumption in summer and winter.

UV Blockage:

Reduction in excessive sunlight, blockage of UV A / B rays.

Transparency:

Different Openness Factors preserve your privacy, preventing "see-through" from outside while maintaining full visibility of the outside.

Perfect Shape:

The H.T. Polyester yarn is completely cylindrical, making it easier to open and close retractable Blinds or Awnings without fabric displacement.

Its flexibility and cylindrical shape give Polyester significant advantages compared to other materials such as Fiberglass. Polyester prevents breaking or fraying and gives the product a more consistent look even after years of exposure to the harshest weather conditions.

Easy Fabrication:


Fray-free RecScreen® products do not need special cutting equipment. No tape is needed to secure the edges of the Polyester Screen, saving time and expense.

Stability and Durability:

By using only high quality Polyester and PVC pigments, RecScreen® won't fade or break down when exposed to continuous sunlight and offers unsurpassed dimensional stability for demanding applications like retractable zipper screens. (Color fastness factor 7-8, UNE ISO 105 B02).

Healthy:

Free from glass fiber, lead, PFAS, or any other toxic heavy material commonly used. No unpleasant smells and free from any gassing substances.



RECASENS USA

BCN 1886

www.recasensusa.com