

## SC2000 MASTERSHADE®

#### **Exterior Rolling Screen / small box**

The SC2000 is our small box traditional exterior retractable vertical rolling screen system. The fabric runs inside vertical guide Tracks or Cable Guides by means of gravity. When the shade is retracted the fabric is stored in the built-in protective box. The weighted hem bar keeps the fabric taut. This Mastershade model is made of the highest quality extruded aluminum.


The SC2000 has a 4" x 4 1/4" Cassette box.

Туре	Standard Frame Colors	Standard Widths	Standard Heights	Recommended Applications	Recommended Fabrics
Screen Exterior Retractable	9 standard Sunair colors	Through 14' 24' with split	Through 14' Depending on Fabric type	Residential & Commercial Windows,	Various Mesh & Acrylic Fabrics

- Small standard box or Waterfall configuration available.
- Capable of wider widths with fabric split.
- Gear or Motorized operation.
- Cabled or standard track available.
- Optional flange track available to cover fabric gap between track and fabric edge.



## **SC2000 Mastershade® Installations**



















#### SC2000 Standard Box With Standard Track and cable Guides




**STANDARD BOX** is available with both track and cable guides see above.





Standard track






Cable guide

bracket


#### Stand-

ard Track showing gap in fabric



GEAR

**STANDARD BOX** 



OUTSIDE GEAR

STANDARD BOX

#### SIZES FOR SC2000 Mastershade®

Hem Bar

Max width 14 ft. with single fabric Max width 24 ft. with split fabric (2 ea. fabrics) Max drop 9 & 14 ft. (Depending on fabric & size)

#### **GEAR OPERATION:**

Operate the shade with a standard hand crank (4:1 ratio gear) from the inside or outside.

#### **MOTORIZED OPERATION:**

Use either a standard hardwire motor or RTS Altus remote motor.

Minimum widths: Standard motor 26"

Altus motor 29"

Note: Manual CMO override is not available.

#### MEASURING SC2000:


4 1/4" ---- $(\mathcal{F})$ HEIGHT


Width: Determine the desired width. The width you order must be the measurement outside of track to outside of track. If possible, add 1 1/2" on each side for proper window coverage by the fabric. There will be a small 3/8" gap between the fabric edge and the track on each side unless you use Flange track which overlaps the fabric gap. If using cable quides instead of track, allow roughly 1  $\frac{1}{2}$ " less fabric on each side. Adjust the width of the cassette accordingly to cover the opening regardless if using track or cables.

Height: Determine the height of the window or opening. The fabric or screen should cover the height of the window. The height of the delivered screen includes the cassette height of 4". To calculate the height of the shade, add the height of the cassette (4") and the hem bar (2") to the total height of the window measurement (See illustration to the Left). Note: Pay attention to casement windows that will interfere with the hem bar when the shade is retracted (In such a case, mount the top of the cassette 6" above the opening window edge). In addition, if the hem bar needs to go below the glass area as not to be seen through the glass when the shade is lowered, add another 2" to the height, for a total of 8" (Glass height plus 8").

position

STANDARD TRACK SC2000





W A L L

## **BENEFITS OF SOLAR SCREENS**



Screen fully lowered down

- Reduces indoor temperatures and saves energy cooling your space.
- Cuts down on solar glare while retaining your view depending on mesh fabric type and openness factor.
- Cuts down on interior fading of floors, carpets and furniture.
- Can offer complete black out privacy blocking all light.



Screen partially lowered down




Screen partially down showing glare




Screen fully down and no glare

## **BENEFITS OF SOLAR SCREENS cont:**



Solar screens can be installed both on the exterior and interior applications of residential and commercial spaces. The benefit with exterior solar screens is that the fabric blocks the sun before it enters the home or space through the glass. Sometimes it is not feasible to install an exterior screen. In such a case, interior screens offer a good alternative. Interior screens are also more economical.

## **BENEFITS OF EXTERIOR SOLAR SCREENS:**



## FRAME COLORS (STANDARD)

## Screens\*

\*Note: See each model technical page for available frame colors. <u>Available interior screen colors are</u> <u>different than depicted below (see Interior screens).</u>



NOTE: All these colors except Green Ral 6005 and Desert Sand / Ivory are "super durables" which offer better durability compared with standard polyesters powders.



**NOTE:** ACTUAL FRAME COLOR MAY VARY FROM DIGITAL IMAGES






### **ACRYLIC FABRIC COLLECTION**




Fabric covers sewn with Tenara thread.












Graduated

5398/930 Dune / Browi Striped





Grey

bie

#### SOLIDS · TWEEDS · BLOCK STRIPES · FANCY STRIPES · GRADUATED STRIPES

5	Forest Green	4
7	Moss Green	4
8	Medium Green	-
11	Red	
12	Yellow	4
13	Ocean Blue	40
14	Toast	42
15	White	50
24	Black	5
33	Forest Green/White	50
35	Red/White	5
37	Yellow/White	50
47	Brown/Stone	5
52	Tan	50
53	Pale Peach	50
73	Burgundy	50
75	Navy Blue	5
79	Grey	5
81	True Brown	50
84	Dark Terracotta	51
87	Fancy Blue	51
101	Elite Toast	51
102	Cappuccino	5
106	Toffee	5
107	Textured Dark Grey	51
242	Grey/White	53
426	Terracotta	53
439	Dark Grey/White	53
809	Cream/Green	53
878	Beige/White Speckled	53
926	Taupe Classic Solid	534
931	Green/Cream Wide	534
969	Grey Fancy Stripe	
1101	Beige/Stripe Fancy	
1120	Brown/Beige Fancy	537
1150	Rust/Green Multi	
116/15	Medium Blue/White	53
1243	Yellow Multi	539
1302	Sage Tweed	53
1330/512	Carbon Stitch	53
15/1	Beige	539
15/14	Raw	539
15/79	Stone	539
4015/91	Raw Speckled	53
407/11	Burgundy Tweed	53
407/13	Blue Tweed	53

407/14	Toast Classic Tweed
407/16	Moss Classic Tweed
407/3	Green Classic Tweed
407/6	Green Tweed
407/79	Pepper Grey
07/926	Grey Classic Tweed
215/15	Textured Tan
5000/57	Cocoa Stripe
5001/1	Green Graduated
5001/13	Blue Graduated
5001/7	Moss Graduated
5001/73	Burgundy/Grey Graduated
5009/1	Beige/Tan Stripe
5009/14	Brown/Tan Stripe
5011/11	Brick/Natural Fancy
5011/57	Tan/Brown Fancy
	Tan/Green Fancy
5011/7	Natural/Moss Graduated
5071/7	
072/86	Brown/Stone Fancy
5118/62	Yellow/White Fancy
5144/14	Pastel/Natural Fancy
5167/11	Red/Grey Fancy
5167/2	Blue/Grey Fancy
5167/5	Green/Grey Fancy
5173/12	Yellow/Grey Stripe
5304/15	Rose/Grey Stripe
5347/58	Grey/Wheat Multi
5347/79	Platinum Grey Multi
5348/58	Beige/Wheat Multi
5348/79	Grey/Slate Multi
849/106	Brown/Cream Stripe
849/930	Beige/Brown Classic
5369	Charcoal/Brown
5370	Beige/Grey
371/727	Grey/Black Stripe
5374	Smoke/Grey Stripe
5396/78	Green Tweed Stripe
896/930	Hazelnut Stripe
5396/97	Charcoal Tweed Stripe
5397/97	Grey/Black Graduated
898/107	Carbon Blue Blend
898/930	Dune/Brown Stripe
899/107	Dark Grey Tweed
5399/15	Light Grey Stripe
5399/52	Sesame Tweed Stripe
5399/94	Stone/Grey Tweed
	-

5406/52	Coriander Tweed
5406/94	Textured Desert Beige
5407/107	Charcoal/Stone Tweed
5407/15	Textured Silk Grey
5407/17	Sky Tweed
5407/52	Sesame Tweed
5407/94	Desert Grey Tweed
633/79	Grey/Black Fancy
634/51	Grey/Natural Fancy
634/97	Green/Tan Fancy
635/11	Cranberry/Natural Fancy
636/10	Grey/Blue Graduated
636/12	Yellow Graduated
636/14	Brown Elite Stripe
636/5	Green/Beige Fancy
636/84	Terracotta Graduated
638/5	Green/Grey Fancy
639/99	Tan/Natural Fancy
641/10	Blue/Beige Fancy
727/15	Textured Medium Grey
739/701	Sage/Beige Fancy
769/75	Cream/Blue Fancy
782/14	Beige Solid Classic
873/151	Dune Tweed
873/2	Textured Cocoa
939/94	Grey Elite Stripe
940/5	Green Elite Stripe
947/14	Pale Beige Classic
949/91	Brown/Beige Classic
950/24	Grey/Charcoal Classic
951/92	Grey/Navy Classic
967/926	Grey/Charcoal Elite
968/426	Terracotta/Cream Fancy
97/84	Plum
986/106	Textured Beige
986/15	Textured Light Grey
986/727	Textured Pebble Grey
	-






# RecScreen 5000P



#### Specifications

Composition: 15% Polyester, 85% Vinyl Syle: Basket Weave Mesh Weight: 14,75 (oz/yd2) Openness Factor: 5.5 % Fabric Thickness (in): .026 Width: 118" Fire classification: NFPA 701 Test 1, and CA Fire Marshall Title 19, Section 1237.1 Warranty: 5 years exterior Bacteria and Fungal Resistance: AATCC Test Method 100-2004

300 Charcoal / Charcoal





# RecScreen



#### **Specifications**

Composition: 18% Polyester, 82% Vinyl Syle: Twill Mesh Weight: 17,8 (oz/yd²) Openness Factor: 3 % Fabric Thickness (in): .78 mm Width: 118" Fire classification: NFPA 701 Test 1, and CA Fire Marshall Title 19, Section 1237.1 Warranty: 10 Year Limited. Visit www.recasensusa.com for full warranty. Bacteria and Fungal Resistance: AATCC Test Method 100-2004

#### 300 Charcoal / Charcoal




001 White / Linen



002 White / Sable



004 White / Pearl Grey



502 Dark Gray / Sable



503 Dark Gray / Charcoal



307Charcoal

/ Bronze



#### **Exterior Screen Fabric**



Outdoor Screen Fabric. 42% Fiberglass 58% vinyl

3%, 5%, & 10%

Charcoal/Cocoa

930992 Charcoal/Garnet

901901 Grey/Grey

910902

910988

901910 Grey/Sable 30M687

Charcoal/ Cocoa-Fawn

930961

Sable/Wood

Sable/White

10M127 Sable/Sable-Fog

901930 Grey/Charcoal

30M394 Charcoal/ Charcoal-Navy

930993 Charcoal/Forest

930930 Charcoal/ Charcoal



30M394 | Charcoal/Charcoal-Navy 1% 5%

30M394 | Charcoal/Charcoal-Navy



#### **Exterior Screen Fabric**



Outdoor Screen Fabric. 42% Fiberglass 58% vinyl

1% & 5%

Charcoal/ Charcoal-Grey

Charcoal/Charcoal

Charcoal/Garnet



## **Soltis** Horizon 86



14 % Open Screen Mesh

#### **Exterior Screen Fabric**

#### 5 year warranty from Ferrari



## **Exterior Screen Fabric** TEXTILE NONO<sup>™</sup>9 BRAND FABRIC 5 % Open Screen Mesh ShadowTexture Granite **Expresso** Texture White Stone Texture Flat Black Bone Tobacco Charcoal

TEXTILENE<sup>®</sup> nano<sup>™</sup> 95 is a durable, yet lightweight synthetic fabric. It is lighter and finer with the same technical qualities as the original TEXTILENE<sup>®</sup>. TEXTILENE<sup>®</sup> nano<sup>™</sup>95 is excellent for exterior use and can reduce energy costs while blocking up to 95% of the sun's harmful rays.





Sunair is proud to offer the full line of Somfy motors and controls for our awnings and screens program SOMFY RTS features motors with an integrated radio receiver that allows you to operate the awning by remote control with a wall mounted or hand held remote or by smart phone device. With a simple click of your remote, the awning or shade will extend or retract automatically. The manual override Sunea motor is ideal for awnings and the Altus motors is ideal for exterior screens. Each motor can be configured with a cord & plug which can simply be plugged into your patio outlet. They are available in 1.4", 11', 17', & 23' lengths. Altus motor cords depend on motor model and is standard either 6' or 10' pigtail cords. Optional Altus plug in cords are available in 10', 18', and 24 ' lengths. Optional screen motor is Maestria with obstacle detection. Add Tahoma smart phone and table interface.



**ALTUS**®

## SOMFY REMOTES:



One (1) through (16) channel hand held or wall mounted remotes are available. <u>Remotes are available in</u> <u>different colors to suit your style,</u>

<u>please inquire.</u>



Telis hand-held remotes offer convenient and simple operation of every type of motorized application. Channels help organize the motorized products that are operated. Single channel remotes can operate one individual product or one group of motorized products. Multiple channel remotes can handle groups of motorized products.



## **AVAILABLE AUTOMATIC SENSORS & CONTROLS**



SOLIRIS RTS 24V KIT Sun & Wind Sensor

The Soliris RTS Sun and Wind Sensor automatically controls your RTS motorized products based on current weather conditions.



**ONDEIS® WIREFREE** Sun & Rain Sensor

The Rain Sensor is a solar-powered combined rain and sun sensor compatible with Radio Technology Somfy<sup>®</sup> motorized exterior products, including awnings and screens.



Sunis & ThermoSunis Indoor WireFree™ RTS Sensors



## SOMFY MOTOR WIRING



The three (3) wire cords can be wired in parallel and can be ordered with a molded plug to simply plug into an exterior UL approved GFI outlet. The standard four (4) wire cords must be hard wired with a traditional toggle wall switch. Screens can not be ordered with molded plugs on the end.



RTS

#### Radio Technology Somfy

Radio Technology Somfy® (RTS) allows wireless radio control of motorized applications via the RTS family of controls.

Type of power cable RTS

RTS plug in capable motor cord

white = neutral

**Optional molded plug** is available for "awning" motors only




#### All Somfy Motors are UL and CSA Recognized

 All SOMFY motors are UL Recognized and can be found under the following file numbers:

E60495, E60888, E63714








GROUND CONNECTED TO BOX




#### Dimensions



**ALTUS MOTOR** 

506	510	525	535	550
6 Nm	10 Nm	25 Nm	35 Nm	50 Nm
120V / 60HZ				
1.1A	1.3A	1.6A	2.1A	2.1A
38 rpm	38 rpm	20 rpm	20 rpm	14 rpm

## Autosun solar powered motor for screens





The Simu solar powered motor can be utilized with smaller sized exterior solar screens and our small Combi window awnings. The available screen models are the SC2000, SC3000, and SC4000 models with standard track or cables up to 14 ft. wide (Please see your Sunair dealer for options and limitations). This battery powered motor does not require a hardwiring or an electrician. The motor kit comes with a solar panel and can be ordered optional with a rechargeable battery pack. You must add a hand held remote to operate.



### **Somfy TaHoma® RTS Smartphone and Tablet Interface**

The Somfy TaHoma<sup>®</sup> gateway and smart phone app provides convenient and customized control of Somfy powered motorized shades, blinds, and other motorized solutions. Control up to 40 RTS (Radio Technology Somfy) channels using the TaHoma app. Multiple TaHoma devices can be joined for multi-zone control.



- North America app, you can remotely activate both Zigbee and RTS products Supports UP/ DOWN/MY/STOP commands for motorized shades/blinds.
- Supports incremental control for Tilt motors and lighting I Supports ON/OFF commands for control of lighting or other devices powered via the Zigbee Smart Plug Multiple users .





TaHoma<sup>®</sup> RTS

## Bond Home / Smartphone and Tablet Interface

Bond Bridge and Bond Bridge Pro works as a bridge between Wi-Fi and your remotes recorded signal allowing you to operate your Sunair shades, awnings, pergolas, ceiling fans, fireplaces and more with the Bond app. Works with Somfy and other motor manufacturers.



# Remote control from anywhere

Be able to control everything even from outside your home.

#### Bond Bridge

- Works with Alexa, Google Home, and SmartThings,
- Remote Control via Bond Home app
- Works with iPhone or Android
- No installation needed
- Smart home functionality without breaking the bank

#### Bond Bridge Pro: Added features...

- Ethernet port & PoE technology
- Smart home integrations
- Ceiling and wall mount

#### **OPTIONAL:**

• <u>Sidekick for Shades</u>: 5-channel Shade and awning

## **BOND REMOTE SWITCH:**

## Sidekick for Shades/Awnings: 5-channel Shade Keypad




o bond

- Wireless flush mount shade remote.
- Communicates directly with the shade.
- 10-year battery life.
- Set up shade limits no manufacturer remote required.
- This version of Sidekick does not support Scene Keypad functionality.
- 10-year battery life.
- Install with or without a workbox (flush mount).
- 5-channel control.
- Set up shade limits no manufacturer remote required.

## Notes

Note: Sunair<sup>®</sup> reserves the right to change engineering, specifications and prices without notice. Images and Illustrations in the catalog may vary from digital and printed manuals.





## SUNPROOFING AMERICA!



#### MARYLAND LOCATION

Mailing: P.O. Box 1068 Shipping: 7785 Rt. 175 Jessup, MD 20794

Toll Free	800	- 548 -	0408
-----------	-----	---------	------

- Phone: 410 799 1145
- Fax: 410 799 5584

#### www.sunairawnings.com

#### **ARIZONA LOCATION**

Mailing: <u>Same as Jessup</u> Shipping: 3807 West Thomas Rd. Phoenix, AZ 85017

Toll Free	877 - 272 - 3920
Phone:	602 - 272 - 3920
Fax:	602 - 272 - 3925

info@sunairawnings.com