

# SC3000 MASTERSHADE®

### **Exterior Rolling Screen / Large Cassette**

The SC3000 is our large box traditional exterior retractable vertical rolling screen system. The fabric runs inside vertical guide Tracks or Cable Guides by means of gravity. When the shade is retracted the fabric is stored in the built-in protective box. The weighted hem bar keeps the fabric taut. This Mastershade model is made of the highest quality extruded aluminum.

The SC3000 has a 53/8" x 51/8" Cassette box.

Туре	Standard Frame Colors	Standard Widths	Standard Heights	Recommended Applications	Recommended Fabrics
Screen Exterior Retractable	9 standard Sunair colors	Through 18' 24' with split	Through 16' Depending on Fabric type	Residential & Commercial Windows	Various Mesh & Acrylic Fabrics

- Larger standard box screen.
- Capable of wider widths with fabric split.
- Gear or Motorized operation.
- Cabled or standard track available.



## **BENEFITS OF SOLAR SCREENS**



Screen fully lowered down



- Cuts down on solar glare while retaining your view depending on mesh fabric type and openness factor.
- Cuts down on interior fading of floors, carpets and furniture.
- Can offer complete black out privacy blocking all light.



Screen partially lowered down



Screen partially down showing glare



Screen fully down and no glare

## **BENEFITS OF SOLAR SCREENS cont:**



Solar screens can be installed both on the exterior and interior applications of residential and commercial spaces. The benefit with exterior solar screens is that the fabric blocks the sun before it enters the home or space through the glass. Sometimes it is not feasible to install an exterior screen. In such a case, interior screens offer a good alternative. Interior screens are also more economical.

## **SC3000 Mastershade® Installations**











#### SC3000 Large Box With Cable Guides











#### **Standard Track**

Hem bar with recessed fabric cavity hiding the seam

#### **MEASURING SC3000:**



**Width:** Determine the desired width. The width you order is the measurement outside of track to outside of track. If possible, add  $1\frac{1}{2}$  " on each side for proper window coverage by the fabric. There will be a small 1/8" gap between the fabric edge and the track on each side. If using cable guides instead of track, allow roughly  $1\frac{1}{2}$ " less fabric on each side. Adjust the width of the cassette accordingly to cover the opening if using cable guides.

**Height:** Determine the height of the window or opening. The fabric or screen mesh should cover the height of the window. The height of the delivered screen includes the cassette. To calculate the height of the shade, add the height of the cassette (5") and the hem bar (2") to the total height of the window measurement (see to left and below). Note: Watch out for casement windows that will interfere with the hem bar when the shade is retracted (In such a case, mount the top of the cassette 6" above the opening window edge). In addition, if the hem bar needs to go below the glass area as not to be seen through the glass when the shade is lowered, add another 2" to the height, for a total of 9" (Glass height plus 9").

Note: The cassette can be ceiling mounted (see install instructions)





SUMAR & SOLAR SCREENS

**NOTE:** ACTUAL FRAME COLOR MAY VARY FROM DIGITAL IMAGES



# RecScreen 5000P



### Specifications

Composition: 15% Polyester, 85% Vinyl Syle: Basket Weave Mesh Weight: 14,75 (oz/yd2) Openness Factor: 5.5 % Fabric Thickness (in): .026 Width: 118" Fire classification: NFPA 701 Test 1, and CA Fire Marshall Title 19, Section 1237.1 Warranty: 5 years exterior Bacteria and Fungal Resistance: AATCC Test Method 100-2004

300 Charcoal / Charcoal





# RecScreen



#### **Specifications**

Composition: 18% Polyester, 82% Vinyl Syle: Twill Mesh Weight: 17,8 (oz/yd²) Openness Factor: 3 % Fabric Thickness (in): .78 mm Width: 118" Fire classification: NFPA 701 Test 1, and CA Fire Marshall Title 19, Section 1237.1 Warranty: 10 Year Limited. Visit www.recasensusa.com for full warranty. Bacteria and Fungal Resistance: AATCC Test Method 100-2004

#### 300 Charcoal / Charcoal



001 White

/ Linen



002 White / Sable



004 White / Pearl Grey



502 Dark Gray / Sable



503 Dark Gray / Charcoal



307Charcoal

/ Bronze

#### **Exterior Screen Fabric**

## **Soltis** Horizon 86



14 % Open Screen Mesh

	86-2043 Bronze	86 – 2135 Sandy Beige		86 – 2053 Black
86 – 2175 Champagne	86 – 2044 White	86 – 2012 Pepper		86 – 2171 Boulder
	Tachnical pror	ortion	Superio	r elongation and tear resistance
Technical propertiesOpeness factor14%		berties	No deformation during processing	
Weight	and use			
Thickness	0.45 mm — 450 microns Superior a durability		r aesthetic and mechanical Ly	
Width	177 cm - 267 cm — 69.7 in 105.1 in.		Smooth easy roll	finish easy to clean, space saving, ing

## **Exterior Screen Fabric** TEXTILE NONO<sup>™</sup>9 BRAND FABRIC 5 % Open Screen Mesh ShadowTexture Granite **Expresso** Texture White Stone Texture Tobacco Charcoal Flat Black Bone

TEXTILENE<sup>®</sup> nano<sup>™</sup> 95 is a durable, yet lightweight synthetic fabric. It is lighter and finer with the same technical qualities as the original TEXTILENE<sup>®</sup>. TEXTILENE<sup>®</sup> nano<sup>™</sup>95 is excellent for exterior use and can reduce energy costs while blocking up to 95% of the sun's harmful rays.















#### 5348/14 Beige / Grey Multi

774/62 Green / Speckled Fancy



636/5 Green / Beige Fancy



5011/7 Tan / Green Fancy



948/21 Pale / Blue Classic



636/10 Grey / Blue Graduated



5348/79 Grey / Slate Multi



739/701 Sage / Beige Fancy



638/5 Green Grey Fancy



5071/7 Natural/Moss Graduated



951/92 Grey / Navy Classic



641/10 Blue / Beige Fancy



939/79 Yellow / Grey Elite





950/24 Grey / Charcoal Classic 967/926 Grey/Charcoal Elite 634/51 Grey / Natural Fancy



#### 633/79 Grey/ Black Fancy



#### Index Para / Tempotest Sunair Fabric collection SOLIDS • TWEEDS • BLOCK STRIPES • FANCY STRIPES • GRADUATED STRIPES

Pattern	Description	Pattern	Description	Pattern	Description
101 102 106 986/15 727/15 107 986/106 873/2 97/84 407/3 407/16 407/14 407/926 926 782/14 15 15/14 4015/91 15/1 4215/15 52 14 12 53 1302 7 5 407/6 8 13 407/13 75 87 79 407/79 15/79 84 426 11 81 73	Elite Toast Cappuccino Toffee Textured Lt. Grey Textured Med. Grey Textured Dk. Grey Textured Beige Textured Cocoa Plum Green Classic Tweed Moss Classic Tweed Toast Classic Tweed Taupe Classic Tweed Grey Classic Solid Beige Classic Solid Beige Classic Solid White Raw Raw Speckled Beige Textured Tan Tan Toast Yellow Pale Peach Sage Tweed Moss Green Forrest Green Green Tweed Medium Green Ocean Blue Blue Tweed Navy Blue Fancy Blue Grey Pepper Grey Stone Dark Terracotta Terracotta Red True Brown Burgundy	407/11 24 5374 5370 35 33 37 47 969 242 68 439 809 878 116/15 931 5347/58 5348/58 5349/930 636/14 945/97 946/58 947/14 949/91 959/14 959/84 5001/73 1101 636/84 639/99 1120 5009/1 5009/14 5009/14 5011/57 5072/86 5144/14 635/11 5011/11 5304/15 5173/12	Burgundy Tweed Black Smoke / Grey Stripe Beige / Grey Red / White Forest Green / White Forest Green / White Yellow / White Brown / Stone Grey Fancy Stripe Grey / White Black / Grey Dark Grey / White Cream / Green Beige / White Speckled Medium Blue / White Green / Cream Wide Grey / Wheat Multi Beige / Wheat Multi Beige / Wheat Multi Beige / Wheat Multi Beige / Brown Classic Brown Elite Stripe Beige Elite Stripe Beige Classic Brown / Beige Classic Brown / Beige Classic Brown / Beige Classic Beige / Toast Elite Beige / Brick Elite Burgundy / Grey Graduated Beige / Stripe Fancy Terracotta Graduated Tan / Natural Fancy Brown / Beige Fancy Brown / Stone Fancy Pastel / Natural Fancy Cranberry / Natural Fancy Cranberry / Natural Fancy Red / Grey Fancy Rose / Grey Fancy Yellow / Grey Stripe	5118/62 5009/12 1150 5349/5 5368/106 940/5 764/62 774/62 739/701 634/97 635/8 636/5 638/5 5001/1 5001/7 5011/7 5071/7 5167/5 484/3 948/21 951/92 769/75 5167/2 636/10 641/10 5001/13 5348/14 5348/79 939/79 939/94 950/24 967/926 634/51 633/79	Yellow/White Fancy Gold/Tan Stripe Rust / Green Multi Natural / Green Classic Toast / Grey / Rust Green Elite Stripe Green / Tweed Fancy Sage / Beige Fancy Green / Stone Fancy Green / Tan Fancy Green / Stone Fancy Green / Beige Fancy Green / Grey Fancy Green Graduated Moss Graduated Tan / Green Fancy Natural / Moss Graduated Green / Grey Fancy Pale / Blue Classic Grey / Navy Classic Cream / Blue Fancy Blue Graduated Bue / Grey Fancy Grey / Blue Graduated Bue / Grey Fancy Blue / Grey Fancy Grey / Blue Graduated Bue / State Multi Yellow / Grey Elite Grey / Charcoal Classic Grey / Natural Fancy Grey / Black Fancy

## **MOTORIZATION & AUTOMATION**



Sunair is proud to offer the full line of Somfy motors and controls for our awnings and screens program. SOMFY RTS features motors with an integrated radio receiver that allows you to operate the screen by remote control with a wall mounted or hand held remote or by smart phone device. With a simple click of a button on your remote, the shade will lower or retract automatically. The Altus motors is ideal for exterior screens. Manual override motors (CMO) is not available for the SC3000 model.





## AVAILABLE BATTERY OPERATED REMOTES



One (1) through (16) channel hand held or wall mounted remotes are available. <u>Remotes are available in</u> <u>different colors to suit your style,</u> <u>please inquire.</u>

Telis hand-held remotes offer convenient and simple operation of every type of motorized application. Channels help organize the motorized products that are operated. Single channel remotes can operate one individual product or one group of motorized products. Multiple channel remotes can handle groups of motorized products.





Telis 1 Chronis RTS Timer

DecoFlex WireFree™ RTS Wall Switches





Smoove® 1 RTS Surfact Mount Wall Switch

## **AVAILABLE SENSORS & CONTROLS**





EOLIS 3D WIREFREE™ RTS

Wind sensor for lateral Arm Awnings only

The Eolis 3D WireFree<sup>™</sup> RTS Wind Sensor is a wireless, battery powered wind sensor that will automatically retract an awning based on wind generated movements.



SOLIRIS RTS 24V KIT Sun & Wind Sensor

The Soliris RTS Sun and Wind Sensor automatically controls your RTS motorized products based on current weather conditions.



**ONDEIS® WIREFREE** Sun & Rain Sensor

The Rain Sensor is a solar-powered combined rain and sun sensor compatible with Radio Technology Somfy<sup>®</sup> motorized exterior products, including awnings and screens.

The Somfy myLink<sup>™</sup> is a simple device that turns your smartphone or tablet into a sophisticated remote control for motorized products featuring Radio Technology Somfy<sup>®</sup>, allowing you to operate them whether you're home or not. Combine all the benefits of Somfy's RTS hand-held remotes and timers in a convenient app.









Sunis & ThermoSunis Indoor WireFree™ RTS Sensors





Radio Technology Somfy Radio Technology Somfy® (RTS) allows wireless radio control of motorized applications via the RTS family of controls.

## All Somfy Motors are UL and CSA Recognized

• All SOMFY motors are UL Recognized and can be found under the following file numbers:

E60495, E60888, E63714

Warranty



# SOMFY MOTOR WIRING

The three (3) wire cords can be wired in parallel. The standard four (4) wire cords must be wired with a traditional toggle wall switch. <u>Screens can not be ordered with molded plugs on the end.</u>

## Type of power cable



TO BOX

#### Dimensions



# LT50 Altus<sup>®</sup> RTS

506	510	525	535	550
6 Nm	10 Nm	25 Nm	35 Nm	50 Nm
120V / 60HZ				
1.1A	1.3A	1.6A	2.1A	2.1A
38 rpm	38 rpm	20 rpm	20 rpm	14 rpm

## **MAESTRIA OSTACLE**

## **DETECTION EXTERIOR EXTERIOR SCREEN MOTOR**



The SOMFY <u>Maestria obstacle detection motor</u> is the recommended motor to be used on all larger screens with heavier. These motors accurately detects obstacles, stopping after meeting an object traveling up or down. Protects carrier products and prevents fabric damage resulting from screen bunching and slipping from the guides. The motor senses and distinguishes between an actual obstacle and wind, even wind gusts, so it doesn't stop unnecessarily, resulting in fewer service calls and end user peace of mind.

## Autosun solar powered motor for screens





The Simu solar powered motor can be utilized with smaller sized exterior solar screens. The available screen models are the SC2000, SC3000, and SC4000 models with standard track or cables up to 14 ft. wide (Please see your Sunair dealer for options and limitations). This battery powered motor does not require a hardwiring or an electrician. The motor kit comes with a solar panel and can be ordered optional with a rechargeable battery pack. You must add a hand held remote to operate.



## Notes

Note: Sunair<sup>®</sup> reserves the right to change engineering, specifications, and prices without notice. Images and Illustrations in the catalog may vary from digital and printed manuals.





## SUNPROOFING AMERICA!



#### MARYLAND LOCATION

Mailing: P.O. Box 1068 Shipping: 7785 Rt. 175 Jessup, MD 20794

Toll Free	800 -	548 -	0408
-----------	-------	-------	------

- Phone: 410 799 1145
- Fax: 410 799 5584

#### www.sunairawnings.com

#### **ARIZONA LOCATION**

Mailing: <u>Same as Jessup</u> Shipping: 3807 West Thomas Rd. Phoenix, AZ 85017

Toll Free	877 - 272 - 3920
Phone:	602 - 272 - 3920
Fax:	602 - 272 - 3925

## info@sunairawnings.com