


SUNCHOICE[®] Retractable

The Sunchoice® Retractable patio awning model is available in two models the Elite and Classic. The Elite model is available in custom widths both manual and motorized. The Classic model is available only in 19' 6" width and only motorized. The Classic awning is subject to availability at time of ordering.

Туре	Standard Frame Colors	Standard Widths	Standard Projections	Recommended Applications	Recommended Fabrics
ELITE	Mocha, White	12' - 20'	10'	Deck, Patio Retractable	All Tempotest / Para, Stock patterns
CLASSIC	Cream	19'6"	10'	Deck, Patio Retractable	6 each Polyester patterns


3 & 5 year limited frame warranty

Sunchoice® Elite



- Custom widths 12' 20' x 10 ft. projection.
- Aluminum roller tube and powder coated aluminum square bar.
- Double vinyl coated cable arm design.
- All Sunair stock Acrylic PARA fabric patterns.
- Hood optional (Hood depicted above).
- Hoods are one inch wider than unit width.
- Manual operation standard.
- Simu RTS Radio MO motor w/18' cord and remote <u>optional</u> on Right side.
- 5 year limited frame warranty.
- Hood, wind sensor, ceiling brackets & roof brackets optional.
- White or Mocha frame colors available.

*Sunchoice® Classic





- 19'6" widths x 10 ft. projection.
- Steel roller tube and powder coated steel square bar.
- Double vinyl coated cable arm design.
- Choose from 6 each solution dyed polyester fabric patterns.
- Hood included (depicted above).
- Hoods are two inches wider than unit width.
- Dooya MO radio motor w/ 12' cord & remote included on Right side.
- 3 year limited frame warranty.
- Wind sensor, ceiling brackets & roof brackets optional.
- Available with lvory/Cream frame color.

*Available in two models and one width.


*Pending stock & availability:

MEASURING A LATERAL ARM AWNING:

WIDTH:

The width is based upon the size of the deck. Due to the large sizes of some decks it is not always necessary to cover the entire deck. Make sure the wall is free of down spouts, chimneys and electrical conduit. Any object protruding out from the wall will interfere with the roller mechanism. Note the hood is always 1" wider than the width of the awning frame. The fabric width is always 5" less than the awning frame on units up to 20' wide, and 5 $\frac{1}{2}$ " less on units over 20' wide. If the deck faces the West, then projection is important to consider. If the deck faces South, then width is important to consider.

The roller assembly of the SUNAIR $_{\odot}$ measures 8" high without a hood and 10" high with a hood. Be certain that you have at least 8 – 10" of unobstructed mounting surface.



Projection Projection Projection A minimum of 8" of clearance above the door to the gutter is required without a hood, and 10" with a hood.


The SUNAIR® Lateral Arm Awning is designed for residential decks, patios and commercial storefronts. Smaller projections should be used for a storefront awning. The awnings are designed for sun protection; they are not designed to withstand wind or heavy rain and should not be sold for such purposes (see warranty).

Width

PROJECTION:

Determine the ground clearance above the door or window and then determine the desired projection. Refer to the pitch chart on next page for the ideal mounting height and pitch for the desired projection. The greater the pitch on the awning the less projection it will have (see pitch chart). When the awning is extended the front bar should be at least 7 ft. off the deck or patio. On a commercial installation the distance from the ground to the front bar should be at least 8 ft. depending on local codes. The pitch chart indicates that for every 12" of projection of the awning the mounting brackets should be located 3" higher than the front bar when the awning is extended (3/12 rule).

PITCH CHART AND IDEAL MOUNTING HEIGHT



<u>For example</u>: The brackets on an awning with 10' projection needs to be mounted 9'6" from the ground on a residential installation, 10' x $3^{"} = 2'6" \& 2'6" + 7' = 9'6"$). Because the ideal pitch may not always be attained, it is possible to install the awning lower than the ideal pitch. While the "3/12" rule is ideal, it is perfectly fine to install the awning with a 2/12 pitch. A 1/12 pitch is absolute minimum. Maximum pitch is 45°.

Note: A good rule of thumb is never to install a Lateral Arm Awning below 8 feet at the top of the installation bracket. If only eight feet is attainable do not install an awning with more than 10'2" projection. If the installation height is too low or the desired projection is too great for the available space the awning may have to be installed on the roof (see the installation manual for each individual model).

OPTIONS:




ROOF BRACKETS

Optional AU18 aluminum or stainless roof brackets or AU16C ceiling brackets are available if installing on roof or onto soffit.

OPTIONAL HOOD ELITE MODEL ONLY





Note: Classic model has a different model hood included in the price

CLASSIC MODEL Fabric colors: 6 each polyester fabric patterns



NOTE:

All fabrics have standard 8" wave valances. Binding to complement the fabric. All fabric colors may appear different due to print.

ELITE MODEL ONLY









ELITE MODEL / ACRYLIC FABRIC



Fabric covers sewn with Tenara thread.










Graduated


bou Blue Blena - 5398/9

Striped






986/727 Textured Pebble Grey



Note:

"A" style straight valance is available with either binding sewn in at bottom, or bottom hem, without binding. All remaining valance styles must have a binding sewn in at bottom (see binding color chart).



Standard valance styles are listed here. Some styles may vary depending on the pattern and where the stripes fall. If a custom valance is required, include a well-dimensioned sketch with the order as well as instructions on style. Our standard valance is "E", if no valance style is specified, we use "E".

BINDING COLORS



Colori e numerazioni sono identici alle tinte unite del Tempotest ; Coloris et numÈration sont les mÍmes que les unis du Tempotest Colours and colour references correspond exactly to the Tempotest plains range ; Die Farben bzw. die Farbnummer stimmen mit den Tempotest Uni-Farben , berein Colores y numeraciÚn son iquales que los lisos del Tempotest





SOLIDS · TWEEDS · BLOCK STRIPES · FANCY STRIPES · GRADUATED STRIPES

Toast Classic Tweed

5	Farrant Grann	407/44
	Forest Green	407/14
7 8	Moss Green	407/16
0 11	Medium Green	407/3
	Red	407/6
12	Yellow	407/79
13	Ocean Blue	407/926
14	Toast	4215/15
15	White	5000/57
24	Black	5001/1
33	Forest Green/White	5001/13
35	Red/White	5001/7
37	Yellow/White	5001/73
47	Brown/Stone	5009/1
52	Tan	5009/14
53	Pale Peach	5011/11
73	Burgundy	5011/57
75	Navy Blue	5011/7
79	Grey	5071/7
81	True Brown	5072/86
84	Dark Terracotta	5118/62
87	Fancy Blue	5144/14
101	Elite Toast	5167/11
102	Cappuccino	5167/2
106	Toffee	5167/5
107	Textured Dark Grey	5173/12
242	Grey/White	5304/15
426	Terracotta	5347/58
439	Dark Grey/White	5347/79
809	Cream/Green	5348/58
878	Beige/White Speckled	5348/79
926	Taupe Classic Solid	5349/106
931	Green/Cream Wide	5349/930
969	Grey Fancy Stripe	5369
1101	Beige/Stripe Fancy	5370
1120	Brown/Beige Fancy	5371/727
1150	Rust/Green Multi	5374
116/15	Medium Blue/White	5396/78
1243	Yellow Multi	5396/930
1302	Sage Tweed	5396/97
1330/512	Carbon Stitch	5397/97
15/1	Beige	5398/107
15/14	Raw	5398/930
15/79	Stone	5399/107
4015/91	Raw Speckled	5399/15
407/11	Burgundy Tweed	5399/52
407/13	Blue Tweed	5399/94

407/14	TOASL CIASSIC TWEEU
407/16	Moss Classic Tweed
407/3	Green Classic Tweed
407/6	Green Tweed
407/79	Pepper Grey
07/926	Grey Classic Tweed
215/15	Textured Tan
000/57	Cocoa Stripe
5001/1	Green Graduated
001/13	Blue Graduated
5001/7	Moss Graduated
001/73	Burgundy/Grey Graduated
5009/1	Beige/Tan Stripe
009/14	Brown/Tan Stripe
011/11	Brick/Natural Fancy
011/57	Tan/Brown Fancy
5011/7	Tan/Green Fancy
5071/7	Natural/Moss Graduated
072/86	Brown/Stone Fancy
118/62	Yellow/White Fancy
144/14	Pastel/Natural Fancy
167/11	Red/Grey Fancy
5167/2	Blue/Grey Fancy
5167/5	Green/Grey Fancy
173/12	Yellow/Grey Stripe
304/15	Rose/Grey Stripe
347/58	Grey/Wheat Multi
347/79	Platinum Grey Multi
348/58	Beige/Wheat Multi
348/79	Grey/Slate Multi
49/106	Brown/Cream Stripe
49/930	Beige/Brown Classic
5369	Charcoal/Brown
5370	Beige/Grey
71/727	Grey/Black Stripe
5374	Smoke/Grey Stripe
396/78	Green Tweed Stripe
96/930	Hazelnut Stripe
396/97	Charcoal Tweed Stripe
397/97	Grey/Black Graduated
98/107	Carbon Blue Blend
98/930	Dune/Brown Stripe
99/107	Dark Grey Tweed
399/15	Light Grey Stripe
399/52	Sesame Tweed Stripe
399/94	Stone/Grey Tweed

5406/52	Coriander Tweed
5406/94	Textured Desert Beige
5407/107	Charcoal/Stone Tweed
5407/15	Textured Silk Grey
5407/17	Sky Tweed
5407/52	Sesame Tweed
5407/94	Desert Grey Tweed
633/79	Grey/Black Fancy
634/51	Grey/Natural Fancy
634/97	Green/Tan Fancy
635/11	Cranberry/Natural Fancy
636/10	Grey/Blue Graduated
636/12	Yellow Graduated
636/14	Brown Elite Stripe
636/5	Green/Beige Fancy
636/84	Terracotta Graduated
638/5	Green/Grey Fancy
639/99	Tan/Natural Fancy
641/10	Blue/Beige Fancy
727/15	Textured Medium Grey
739/701	Sage/Beige Fancy
769/75	Cream/Blue Fancy
782/14	Beige Solid Classic
873/151	Dune Tweed
873/2	Textured Cocoa
939/94	Grey Elite Stripe
940/5	Green Elite Stripe
947/14	Pale Beige Classic
949/91	Brown/Beige Classic
950/24	Grey/Charcoal Classic
951/92	Grey/Navy Classic
967/926	Grey/Charcoal Elite
968/426	Terracotta/Cream Fancy
97/84	Plum
986/106	Textured Beige
986/15	Textured Light Grey
986/727	Textured Pebble Grey
	_



ELITE MODEL ONLY

SUNAIR[®] / Simu 50 Nm RTS CMO AWNING MOTOR



We offer a "Sunair/Simu motor with our <u>Sunchoice® Elite</u> awning model awnings which is more economical. This motor is a 50 Nm radio RTS motor and is available on the above two models only. This motor kit includes an 18' plug in cord and a one channel hand held remote. All Somfy remotes and electronic controls are compatible and can be added.



SOMFY REMOTES FOR ELITE MODEL:

ELITE MODEL ONLY



held remotes

One (1) through (16) channel hand held or wall mounted remotes are available. <u>Remotes are available in</u> <u>different colors to suit your style,</u>

please inquire.



Situo hand-held remotes offer convenient and simple operation of every type of motorized application. Channels help organize the motorized products that are operated. Single channel remotes can operate one individual product or one group of motorized products. Multiple channel remotes can handle groups of motorized products.





Telis 1 Chronis RTS Timer

DecoFlex WireFree™ RTS Wall Switches

Telis 1 Patio for exterior use



Smoove® 1 RTS

Surfact Mount Wall Switch



Telis 16 RTS Hand-held Remote

AVAILABLE AUTOMATIC SENSORS & CONTROLS ELITE MODEL:





SOLIRIS RTS 24V KIT

Sun & Wind Sensor

The Soliris RTS Sun and Wind Sensor automatically controls your RTS motorized products based on current weather conditions.



ONDEIS® WIREFREE

Sun & Rain Sensor

The Rain Sensor is a solar-powered combined rain and sun sensor compatible with Radio Technology Somfy[®] motorized exterior products, including awnings and screens.



EOLIS 3D WIREFREE™ RTS

Wind sensor for lateral

Arm Awnings only

The

Eolis 3D WireFree[™] RTS Wind Sensor is a wireless, battery powered wind sensor that will automatically retract an awning based

Note:

Classic model has a similar wind sensor avail; able as an option, made by Dooya



Sunis & ThermoSunis Indoor WireFree™ RTS Sensors


ELITE MODEL ONLY

Somfy TaHoma[®] RTS Smartphone and Tablet Interface

The Somfy TaHoma[®] gateway and smart phone app provides convenient and customized control of Somfy powered motorized shades, blinds, and other motorized solutions. Control up to 40 RTS (Radio Technology Somfy) channels using the TaHoma app. Multiple TaHoma devices can be joined for multi-zone control.

ELITE MODEL ONLY

- North America app, you can remotely activate both Zigbee and RTS products Supports UP/ DOWN/MY/STOP commands for motorized shades/blinds .
- Supports incremental control for Tilt motors and lighting I Supports ON/OFF commands for control of lighting or other devices powered via the Zigbee Smart Plug Multiple users .
- Remote access Control4[®] Certified
 Integration with third-party systems over IP
 Compatible with Somfy Synergy[™] API



501





Bond Home / Smartphone and Tablet Interface

ELITE MODEL ONLY

Bond Bridge and Bond Bridge Pro works as a bridge between Wi-Fi and your remotes recorded signal allowing you to operate your Sunair shades, awnings, pergolas, ceiling fans, fireplaces and more with the Bond app. Works with Somfy and other motor manufacturers.



Remote control from anywhere

Be able to control everything even from outside your home.

Bond Bridge

- Works with Alexa, Google Home, and SmartThings,
- Remote Control via Bond Home app
- Works with iPhone or Android
- No installation needed
- Smart home functionality without breaking the bank

Bond Bridge Pro: Added features...

- Ethernet port & PoE technology
- Smart home integrations
- Ceiling and wall mount

OPTIONAL:

• <u>Sidekick for Shades</u>: 5-channel Shade and awning

BOND REMOTE SWITCH:

Sidekick for Shades/Awnings: 5-channel Shade Keypad




o bond

- Wireless flush mount shade remote.
- Communicates directly with the shade.
- 10-year battery life.
- Set up shade limits no manufacturer remote required.
- This version of Sidekick does not support Scene Keypad functionality.
- 10-year battery life.
- Install with or without a workbox (flush mount).
- 5-channel control.
- Set up shade limits no manufacturer remote required.

Notes

Note: Sunair[®] reserves the right to change engineering, specifications and prices without notice. Images and Illustrations in the catalog may vary from digital and printed manuals.





SUNPROOFING AMERICA!



MARYLAND LOCATION

Mailing: P.O. Box 1068 Shipping: 7785 Rt. 175 Jessup, MD 20794

Toll Free	800	- 548 -	0408
-----------	-----	---------	------

- Phone: 410 799 1145
- Fax: 410 799 5584

www.sunairawnings.com

ARIZONA LOCATION

Mailing: <u>Same as Jessup</u> Shipping: 3807 West Thomas Rd. Phoenix, AZ 85017

Toll Free	877 - 272 - 3920
Phone:	602 - 272 - 3920
Fax:	602 - 272 - 3925

info@sunairawnings.com